UL Product iQ®



Model PC-115P(+)

File Number: E56070

Yellow Card[™]



COMPANY

CHI MEI CORPORATION

No 398 Sec 1 Zhongzheng Rd Rende District Tainan City, 717010 Taiwan

MODEL INFO

PC-115P(+)

Polycarbonate (PC) "WONDERLITE", furnished as pellets

(+) – Indicate 0~0.5% acid scavengers.

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
0.4 mm, Color: ALL	V-2	
1.5 mm, Color: ALL	V-2	
2.5 to 2.8 mm, Color: ALL	V-2	
3.0 mm, Color: ALL	НВ	

ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
0.4 mm, Color: ALL	V-2	
1.5 mm, Color: ALL	V-2	
2.5 to 2.8 mm, Color: ALL	V-2	
3.0 mm, Color: ALL	HB40	

ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
0.4 mm	PLC 4	

1.5 mm	PLC 2	
2.5 to 2.8 mm	PLC 2	
3.0 mm	PLC 2	
High Amp Arc Ignition (HAI)		UL 746A
0.4 mm	PLC 4	
1.5 mm	PLC 4	
2.5 to 2.8 mm	PLC 3	
3.0 mm	PLC 3	
Comparative Tracking Index (CTI)	PLC 2	UL 746A
ligh Voltage Arc Tracking Rate (HVTR)	PLC 2	
ligh Voltage, Low Current Arc Resistance	PLC 6	
HERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
0.4 mm	80 °C	
1.5 mm	120 °C	
1.5 mm 2.5 to 2.8 mm		
	120 °C	
2.5 to 2.8 mm 3.0 mm	120 °C 120 °C	UL 746B
2.5 to 2.8 mm 3.0 mm	120 °C 120 °C	UL 746B
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact	120 °C 120 °C 120 °C	UL 746B
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm	120 °C 120 °C 120 °C	UL 746B
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm 1.5 mm	120 °C 120 °C 120 °C 80 °C 105 °C	UL 746B
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm 1.5 mm 2.5 to 2.8 mm 3.0 mm	120 °C 120 °C 120 °C 120 °C 105 °C 105 °C	UL 746B UL 746B
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm 1.5 mm 2.5 to 2.8 mm 3.0 mm	120 °C 120 °C 120 °C 120 °C 105 °C 105 °C	
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm 1.5 mm 2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Strength	120 °C 120 °C 120 °C 120 °C 105 °C 105 °C 105 °C	
2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Impact 0.4 mm 1.5 mm 2.5 to 2.8 mm 3.0 mm Relative Thermal Index - Mechanical Strength 0.4 mm	120 °C 120 °C 120 °C 120 °C 105 °C 105 °C 105 °C	

Report Date: 2001-09-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."