



Model PA-756H(a)  
File Number: E56070



COMPANY

CHI MEI CORPORATION

No 398 Sec 1 Zhongzheng Rd  
Rende District  
Tainan City, 717010 Taiwan

MODEL INFO

PA-756H(a)  
Acrylonitrile Butadiene Styrene (ABS) "POLYLAC", furnished as pellets  
(a) – Ball pressure temperature is in accordance with IEC 60695-10-2 Method B.

| FLAMMABILITY PROPERTIES         | VALUE | TEST METHOD     |
|---------------------------------|-------|-----------------|
| Flammability                    |       | ANSI/UL 94      |
| 1.5 mm, Color: ALL              | HB    |                 |
| 3.0 mm, Color: ALL              | HB    |                 |
| ISO/IEC FLAMMABILITY PROPERTIES | VALUE | TEST METHOD     |
| Flammability                    |       | IEC 60695-11-10 |
| 1.5 mm, Color: ALL              | HB75  |                 |
| 3.0 mm, Color: ALL              | HB40  |                 |
| ELECTRICAL PROPERTIES           | VALUE | TEST METHOD     |
| Hot-wire Ignition (HWI)         |       | UL 746A         |
| 1.5 mm                          | PLC 4 |                 |
| 3.0 mm                          | PLC 3 |                 |
| High Amp Arc Ignition (HAI)     |       | UL 746A         |
| 1.5 mm                          | PLC 0 |                 |
| 3.0 mm                          | PLC 0 |                 |

|                                              |              |                    |
|----------------------------------------------|--------------|--------------------|
| Comparative Tracking Index (CTI)             | PLC 0        | UL 746A            |
| High Voltage Arc Tracking Rate (HVTR)        | PLC 0        |                    |
| High Voltage, Low Current Arc Resistance     | PLC 6        |                    |
| <b>THERMAL PROPERTIES</b>                    | <b>VALUE</b> | <b>TEST METHOD</b> |
| Relative Thermal Index - Electrical Strength |              | UL 746B            |
| 1.5 mm                                       | 85 °C        |                    |
| 3.0 mm                                       | 85 °C        |                    |
| Relative Thermal Index - Mechanical Impact   |              | UL 746B            |
| 1.5 mm                                       | 80 °C        |                    |
| 3.0 mm                                       | 80 °C        |                    |
| Relative Thermal Index - Mechanical Strength |              | UL 746B            |
| 1.5 mm                                       | 85 °C        |                    |
| 3.0 mm                                       | 85 °C        |                    |
| Ball Pressure Temperature                    | 90 °C        |                    |
| <b>IMPACT PROPERTIES</b>                     | <b>VALUE</b> | <b>TEST METHOD</b> |
| Charpy Impact                                | 0.10 kJ/m²   | ISO 179-1          |

Report Date: 1983-06-23

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."