



Component - Plastics

File Number: E67171

LG CHEM LTD
20 YOIDO-DONG
YONGDUNGPO-GU
SEOUL, 150-721 Republic of Korea



YG569(#)

Acrylic/Acrylonitrile Butadiene Styrene (Acrylic/ABS), pellets

(#) - May be followed by optional suffix letter from A-Z incl., except F, and except Grades HT700B, LI912A, AF303G, AF303S, XR404T, XR407D, XR407E, HF380X, XR404E, XR404-G, XR404-P and LUMILOY GN2108FI.

Flammability	Value	Test Method
Flame Rating		
1.5 mm, ALL	HB	UL 94
3.2 mm, ALL	HB	UL 94
3.2 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.5 mm	PLC 4	
3.2 mm	PLC 4	
High Amp Arc Ignition (HAI)		UL 746
1.5 mm	PLC 0	
3.2 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746
Arc Resistance	PLC 5	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	50.0 °C	
3.2 mm	50.0 °C	
RTI Imp		UL 746
1.5 mm	50.0 °C	
3.2 mm	50.0 °C	
RTI Str		UL 746
1.5 mm	50.0 °C	
3.2 mm	50.0 °C	